

Product Data Sheet



K-CORR[®] G-1107 (Formerly KX1107)

Science Road
Norwalk, CT 06852
(800) 431-7900
Fax: (203) 866-0425
E-Mail: lad@kingindustries.com

K-CORR G-1107 is a proprietary ashless rust inhibitor/antiwear additive system developed for industrial and automotive greases.

CHEMICAL

COMPOSITION: Proprietary ashless rust inhibitor and antiwear additive.

APPEARANCE: Light yellow/amber viscous liquid.

TYPICAL

PROPERTIES:	Nitrogen Content	3.4%
	Phosphorus Content	4.7%
	Viscosity @ 40°C (ASTM D 445, DIN 51 550)	930 mm ² /s (cSt)
	Viscosity @ 100°C (ASTM D 445, DIN 51 550)	34 mm ² /s (cSt)
	Density @ 15.6°C (ASTM D 4052)	0.95 g/ml
	Weight Per Gallon @ 25°C	7.86 lbs
	Flash Point, COC (ASTM D 92, DIN 51 376)	98°C (208°F)

Note: The above data are not specifications.

APPLICATIONS: Greases

Typical Treat Levels

0.25% - 3.00%

K-CORR G-1107 is a metal free rust inhibitor with excellent antiwear properties. **K-CORR G-1107** is especially suitable to fulfill rust requirements in greases, e.g., Emcor test with 5% synthetic sea water.

ADVANTAGES:

- * Excellent rust protection
- * Excellent antiwear performance
- * Good thermal and hydrolytic stability
- * Excellent solubility in mineral oils, synthetic oils, and greases
- * Effective at very low treat levels
- * Excellent compatibility with all types of conventional functional additives
- * Low odor
- * Easy to handle

(see reverse side)

K-CORR[®] G-1107
(Formerly KX1107)

TEST RESULTS: Technical reports are available from King Industries and can be requested by contacting the offices shown below.

SOLUBILITY: Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

STANDARD PACKAGING: 400 lbs (181 kg) closed head drum.

STORAGE CONDITIONS: Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

SHELF LIFE: Best if used within 12 months from the date of manufacture.

HANDLING: Avoid all personal contact. Observe good personal hygiene. For additional information, it is advised to consult the Material Safety Data Sheet (MSDS) for **K-CORR G-1107**.

REGISTRATION: Please refer to the Material Safety Data Sheet.

For Samples or Technical Service, contact King Industries or your King representative.

King Industries, Inc.
Science Road
Norwalk, CT 06852-0588
Tel: 203-866-5551
Fax: 203-866-0425
E-mail: LAD@kingindustries.com

King Industries International, Inc.
Noordkade 64, 2741 EZ Waddinxveen
The Netherlands
Tel: +31-182-631360
Fax: +31-182-621002
E-mail: info@kingintl.nl

v:\lad\TechnicalLiterature\CumtTDS\KCORR\ G1107_02
Revision date: 27 JUL 2004

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.