Additives for coatings and printing inks

DISPARLON

December 2020

DISPARLON 6250

(Anti-Slumping agent for Sealants & Adhesives)

DISPARLON 6250 is a powdered thixotropic agent based on amide wax.

When dispersed along with heating these products build up strong thixotropic network in the vehicle and prevent slumping of sealants and adhesives.

ADVANTAGES

- Easily imparts strong anti-slumping property by dispersed with heat.
- Give uniform adhesion by preventing slumping.
- Composed of 100% organic matter, still these products can provide good handling at the application and manufacturing process.

APPLICATIONS

Recommended for sealants (Modified silicone, Urethane, etc) and Epoxy adhesive systems.

INCORPORATION

Additive levels: $0.5\sim5.0\%$ by total formulation. This recommended level can be used for

orientation. The optimal level should be determined by your laboratory tests.

Dispersing equipment: Kneader, Planetary mixer or Twin screw extruder is recommended.

Dispersing temperature: Adjust the temperature in the range of 50~120 °C. However, dispersing

temperature is depending on the resin and other components. We therefore

recommend 50~100 °C.

TYPICAL PROPERTIES

Appearance	White to light yellow powder
Non-volatile matter	More than 98% by wt of total
Melting point	128 ℃
Bulk density	0.15
Density	1.01 g/cm3
Particle size	Less than 15 μ m

