

DISPARLON

February 2019

DISPARLON AQ-633E

(Rheology control agent for waterborne systems)

DISPARLON AQ-633E is a rheology control agent composed of a polyamide. DISPARLON AQ-633E forms a network structure by interacting with paint components in a coating system, prevents settling and hard caking, and improves pigment orientation. Unlike general waterborne thickeners, DISPARLON AQ-633E can provide high thixotropic property without excess viscosity increasing.

ADVANTAGES

- Excellent anti-settling property
- Imparts high thixotropic property without excess viscosity increasing
- Improve the orientation of metallic pigments

APPLICATIONS

DISPARLON AQ-633E can be used in a wide range of waterborne coating systems.

INCORPORATION

Additive levels : 1.0~5.0% by weight on total formulation.

Method : Can be added at each production stage. Post-addition at a final production stage with a dissolver is recommended.

Keep temperature from a room temperature up to 40°C during dispersing.

TYPICAL PROPERTIES

Appearance	Yellow paste
Non-volatile matter	22.5% by wt.
Amine	N, N-dimethylethanolamine
Solvent	Water / Propylene glycol monomethyl ether
Acid value	24.0

STORAGE

- Keep from freezing. Freezing causes degradation of quality and performance.
- Do not heat. Store below 40°C. Heating causes degradation of quality and performance.



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2015 All Rights Reserved By Kusumoto Chemicals, Ltd.