


K-STAY® Series

Rheology Modifiers For Solventborne Coatings

K-STAY 500 Series are pourable, liquid rheology modifiers based on unique sulfonate technology for pigmented and filled systems that need thermal anti-sag. Benefits include:

- 🏷️ Excellent anti-settle & anti-sag performance
- 🏷️ High gloss and gloss retention
- 🏷️ High efficiency - low use levels
- 🏷️ Ease of use - pourable liquids

Solvent Based Systems



Pourable liquid

Applications

- 2K urethane
- Moisture cure
- Bake finishes
- Protective
- Monocoat
- General industrial




K-STAY 500 SERIES

	Product	Composition	% Solids	Treat Rate	Attributes / Uses
SOLVENT BASED	501	Overbased Calcium Sulfonate Light Aromatic Naphtha	50	1-5%	For solventborne systems, including polyester/melamine, acrylic/melamine, alkyd/melamine, 2K urethanes and epoxies.
	511	Sulfonate Light Aromatic Naphtha	50	1-5%	Ultra high efficiency in TiO2 containing paints. Excellent gloss in urethane formulations.
	555	Overbased Calcium Sulfonate Light Aromatic Naphtha - MS	57	1-5%	General purpose anti-sag and anti-settling for solventborne systems. Economical, efficient and easy to use.

K-STAY® Performance

Thermal Sag Control


Polyester/Melamine Bake
 Step gap applicator: 6-12mils
 Cure schedule: 15 mins. @ 150°C




K-STAY® vs. Conventional Rheology Modifiers

Thermal Sag Control

2K Polyurethane
 Step gap applicator: 6-12mils
 Cure schedule: Ambient



Gloss Performance



Contact Information

Global Headquarters
Tech. Service, R&D, & Sales
 King Industries, Inc.
 1 Science Rd.
 Norwalk, CT 06852, USA
 Phone: 1-203-866-5551

www.kingindustries.com



K-STAY_flyer:TVS3/2022

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.