

Product Data Sheet

NA-LUBE[®] ADTC



Science Road
Norwalk, CT 06852
(800) 431-7900
Fax: (203) 866-0425
E-Mail: lad@kingindustries.com

NA-LUBE ADTC is a unique ashless dithiocarbamate offering extreme pressure, antiwear and antioxidant properties.

CHEMICAL

COMPOSITION: Methylene-bis-(dibutyldithiocarbamate).

APPEARANCE: Light brown moderately viscous liquid.

TYPICAL

PROPERTIES:	Sulfur Content	30.0%
	Nitrogen Content	6.5%
	Pour Point (ASTM D 97)	-13°C (9°F)
	Viscosity @ 40°C (ASTM D 445, DIN 51 550)	370 mm ² /s (cSt)
	Viscosity @ 100°C (ASTM D 445, DIN 51 550)	15 mm ² /s (cSt)
	Density @ 15.6°C (ASTM D 4052)	1.05 g/ml
	Weight Per Gallon @ 25°C	8.8 lbs
	Flash Point, COC (ASTM D 92, DIN 51 376)	180°C (356°F)

Note: The above analytical data are not specifications.

	<u>Typical Treat Levels</u>
APPLICATIONS:	
Heavy Metal-Free Greases	2.5% - 5.0%
Industrial Gear Oils	0.8% - 1.5%
Hydraulic Fluids	0.5% - 1.0%
EP-Turbine Oils	0.5% - 1.0%
Automotive Gear Oils	3.0% - 7.0%

NA-LUBE ADTC is an ashless multifunctional additive that can be used as an extreme pressure, antiwear and antioxidant additive in lubricants and greases where heavy metals are not desired. Because of its chemical nature, **NA-LUBE ADTC** is ideally suited for formulating antimony-free, lead-free and low ash EP greases. Because **NA-LUBE ADTC** exhibits outstanding antiwear and antioxidant properties, it can also be used as an efficient additive for manufacturing industrial gear oils, hydraulic fluids and rust and oxidation oils. Combinations of **NA-LUBE ADTC** with **NA-LUBE AO-130** and **K-CORR[®] 1031** will help to achieve optimum results. A treat level of approximately 1.0% of **NA-LUBE ADTC** in an appropriate base oil will achieve more than 12 load stages on the FZG test rig. **NA-LUBE ADTC** also exhibits good demulsification properties and does not negatively influence AFNOR filtration test results.

(see reverse side)

NA-LUBE[®] ADTC

ADVANTAGES:

- * Multifunctional additive with extreme pressure, antiwear and antioxidant properties
- * Outstanding demulsibility and good thermal stability
- * Excellent solubility properties in highly paraffinic base stocks

TEST RESULTS: Technical reports are available from King Industries and can be requested by contacting the offices shown below.

SOLUBILITY: Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

STANDARD PACKAGING: 450 lbs (204 kg) closed head drum.

STORAGE CONDITIONS: Formation of haze or crystallization may occur during storage under long term freezing conditions. If this occurs, warming to 40-50°C with agitation will reconstitute the product. Avoid heating above 60°C. Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

SHELF LIFE: Best if used within 2 years from the date of manufacture.

HANDLING: Avoid all personal contact. Observe good personal hygiene. For additional information, it is advised to consult the Safety Data Sheet (SDS) for **NA-LUBE ADTC**.

REGISTRATION: Please refer to Section 15 of the Safety Data Sheet for information.

For Samples or Technical Service, contact King Industries or your King representative.

Global Headquarters

Tech. Services, R&D and Sales

King Industries, Inc.
Science Road
Norwalk, CT 06852-0588
Tel: 203-866-5551
Fax: 203-866-0425
E-mail: LAD@kingindustries.com

European Tech. Sales Office

King Industries International, Inc.
Science Park 402
1098 XH Amsterdam
The Netherlands
Tel: +31-20-723-1970
E-mail: info@kingintl.nl

China Sales Office

Dalian Mingruida Technical Consulting Co., Ltd
Building 51, 20 Shuxiang Street
Dalian, China
Tel: +86-15941108485
Email: Hui.Wang@Kingindustries.com

NA-LUBE[®] and K-CORR[®] are registered trademarks of King Industries, Inc.

v:\lad\Technical Literature\CurntTDS\NALUBE\ADTC_05
Revision date: 21 AUG 2019

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.