

Product Data Sheet



NA-LUBE[®] EP-5425

Science Road
Norwalk, CT 06852
(800) 431-7900
Fax: (203) 866-0425
E-Mail: lad@kingindustries.com

NA-LUBE EP-5425 is a light colored, low odor sulfurized olefin/fatty oil with excellent extreme pressure properties for use in industrial lubricants, greases and metalworking fluids.

CHEMICAL

COMPOSITION: Sulfurized olefin/fatty oil.

APPEARANCE: Brown clear liquid.

TYPICAL

PROPERTIES:	Sulfur Content	26.7%
	Active Sulfur Content (ASTM D1662)	17.0%
	Color (ASTM D1500 neat)	5.5
	Viscosity @ 40°C (ASTM D445, DIN 51 550)	790 mm ² /s (cSt)
	Density @ 15°C (ASTM D941)	1.04 g/ml
	Weight Per Gallon @ 25°C	8.7 lbs.
	Flash Point, COC (ASTM D92, DIN 51 376)	>155°C (>311°F)

Note: The above analytical data are not specifications.

		<u>Typical Treat Levels</u>
APPLICATIONS:	Metalworking Fluids	4.0% - 15.0%
	Water Miscible Metalworking Concentrates	5.0% - 20.0%
	Industrial Gear Oils	1.0% - 2.0%
	Slideway Oils	1.0% - 5.0%
	Greases	2.0% - 5.0%

NA-LUBE EP-5425 is a low odor, light colored sulfur carrier based on olefin/fatty oil chemistry. **NA-LUBE EP-5425** provides excellent extreme pressure and antiwear properties when used in combination with appropriate antiwear additives in mineral oils and greases. **NA-LUBE EP-5425** is highly suitable for heavy duty drilling and cutting operations.

NA-LUBE EP-5425's unique chemistry gives it outstanding solubility in naphthenic, Group I and II base oils. When used in combination with metal-containing or ashless phosphorus-type antiwear and lubricity additives, **NA-LUBE EP-5425** is an outstanding alternative to chlorinated paraffins in metalworking fluids.

(see reverse side)

NA-LUBE® EP-5425

- ADVANTAGES:**
- * **Good extreme pressure properties**
 - * **Light color, low odor**
 - * **Compatible with ZnDTP's**
 - * **Easy handling, low viscosity**
 - * **Good solubility properties in Group I and Group II base oils**
- TEST RESULTS:** Technical reports are available from King Industries and can be requested by contacting the offices shown below.
- SOLUBILITY:** Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.
- STANDARD PACKAGING:** 440 lbs (200 kg) closed head drum.
- STORAGE CONDITIONS:** Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 30°C (86°F)
- SHELF LIFE:** Best if used within 18 months from the date of manufacture.
- HANDLING:** Avoid all personal contact. Observe good personal hygiene. For additional information, it is advised to consult the Safety Data Sheet (SDS) for **NA-LUBE EP-5425**.
- REGISTRATION:** Please refer to Section 15 of the Safety Data Sheet for information.

For Samples or Technical Service, contact King Industries or your King representative.

WWW.KINGINDUSTRIES.COM

Global Headquarters

Tech. Services, R&D and Sales

King Industries, Inc.
Science Road
Norwalk, CT 06852-0588
Tel: 203-866-5551
Fax: 203-866-0425

European Tech. Sales Office

King Industries International, Inc.
Science Park 402
1098 XH Amsterdam
The Netherlands
Tel: +31-20-723-1970

China Sales Office

Dalian Mingruida Technical Consulting Co., Ltd
Building 51, 20 Shuxiang Street
Dalian, China
Tel: +86-15941108485

NA-LUBE® is a registered trademark of King Industries, Inc.

v:\ad\Technical Literature\CumtTDS\NALUBE EP\EP5425_07
Revision date: 6 JUL 2023

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.