

# Product Data Sheet

## NA-LUBE<sup>®</sup> KR-007A



Science Road  
Norwalk, CT 06852  
(800) 431-7900  
Fax: (203) 866-0425  
E-Mail: lad@kingindustries.com

**NA-LUBE KR-007A** is a specialty additive for high performance lubricants offering outstanding solubility plus excellent hydrolytic and thermo-oxidative stability.

### CHEMICAL

**COMPOSITION:** Proprietary alkylated aromatic.

**APPEARANCE:** Light amber liquid.

### TYPICAL

<b>PROPERTIES:</b>	Viscosity @ 40°C (ASTM D445, DIN 51 550)	22 mm <sup>2</sup> /s (cSt)
	Viscosity @ 100°C (ASTM D445, DIN 51 550)	3.8 mm <sup>2</sup> /s (cSt)
	Viscosity Index (Calculated)	26
	Pour Point (ASTM D97)	-48°C (54.4°F)
	Aniline Point (ASTM D611)	40°C (104°F)
	Density @ 25°C (ASTM D4052)	0.91
	Weight Per Gallon @ 25°C	7.6 lbs
	Flash Point, COC (ASTM D92, DIN 51 376)	206°C (403°F)

Note: The above analytical data are not specifications.

<b>APPLICATIONS:</b>	Aviation Hydraulic Fluids	Compressor Oils
	Crankcase Oils	Greases
	High Temperature Turbine Oils	Refrigeration Oils
	Other High Performance Applications	Gear Oils

**NA-LUBE KR-007A** is a synthetic alkyl aromatic additive with excellent thermo-oxidative and hydrolytic stability. **NA-LUBE KR-007A** can be used as a solubility modifier in formulations blended with low polarity base oils, including silicone oils, or severely hydrotreated base stocks to enhance additive response. The recommended treat level of **NA-LUBE KR-007A** as a solubility modifier and as a performance enhancer is between 5.0% and 15.0% depending on the application.

- ADVANTAGES:**
- \* **Base oil solubility modifier**
  - \* **Improves additive response**
  - \* **Excellent thermo-oxidative stability**
  - \* **Excellent hydrolytic stability**

(see reverse side)

# NA-LUBE® KR-007A

**SOLUBILITY:** Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended that the solubility in the base oils used and the compatibility with other additives be verified.

**STANDARD PACKAGING:** 400 lbs (181 kg) closed head drum.

**STORAGE CONDITIONS:** Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

**SHELF LIFE:** Minimum of 24 months from the date of manufacture, when stored at the above conditions in the original container.

**HANDLING:** Avoid all personal contact. Observe good personal hygiene. For additional information, it is advised to consult the Safety Data Sheet (SDS) for **NA-LUBE KR-007A**.

**REGISTRATION:** Please refer to Section 15 of the Safety Data Sheet for information.

For Samples or Technical Service, contact King Industries or your King representative.

King Industries, Inc.  
Science Road  
Norwalk, CT 06852-0588  
Tel: 203-866-5551  
Fax: 203-866-0425  
E-mail: LAD@kingindustries.com

King Industries International, Inc.  
Science Park 402,  
1098 XH Amsterdam  
The Netherlands  
Tel: +31-20-723-1970  
E-mail: info@kingintl.nl

NA-LUBE® is a registered trademark of King Industries, Inc.

v:\vad\TechnicalLiterature\CumtTDS\NALUBE\KR007A\_04  
Revision date: 01 MAY 2017

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.