

Product Data Sheet

NA-LUBE[®] AW-6509



Science Road
Norwalk, CT 06852
(800) 431-7900
Fax: (203) 866-0425
E-Mail: lad@kingindustries.com



Nonfood Compounds
(Category Code: HX-1)
(Registration #149707)

[SAMPLE REQUEST](#)

NA-LUBE AW-6509 is an ashless antiwear and extreme pressure additive for industrial and automotive lubricants.

CHEMICAL

COMPOSITION: Triphenyl phosphorothionate.

APPEARANCE: White powder.

TYPICAL

PROPERTIES:	Sulfur Content	9.3%
	Phosphorus Content	8.9%
	Melting Point (DSC)	52°C
	Purity (HPLC)	98.5% min.
	Volatile (Gravimetric)	0.5% max.
	Density @ 25°C (ASTM D 2638)	1.19 g/cm ³
	Flash Point (Pensky Martens)	> 200°C

Note: The above analytical data are not specifications.

		<u>Typical Treat Levels</u>
APPLICATIONS:	Antiwear hydraulic fluids	0.20% - 1.00%
	Greases	0.20% - 1.00%
	Synthetic lubricants	0.20% - 1.00%
	Engine Oils	0.30% - 1.00%

NA-LUBE AW-6509 is an ashless multifunctional additive that provides excellent antiwear and EP properties to mineral oil and most synthetic lubricants. **NA-LUBE AW-6509** is especially suited for formulating ashless lubricants that require high temperature performance.

NA-LUBE AW-6509 has better antiwear and frictional properties than a secondary ZnDTP and is not aggressive toward copper.

ADVANTAGES:

- * **Excellent thermal and hydrolytic stability**
- * **Offers low coefficient of friction**
- * **Compliant with the Food and Drug Administration Regulation 21 CFR 178.3570 up to a treat level of 0.5% by weight**
- * **Shows synergy in FZG performance with NA-LUBE AW-6400 FG**
- * **Responds synergistically with K-CORR 100 series to four ball wear performance.**

(see reverse side)

NA-LUBE AW-6509

SOLUBILITY: Soluble in mineral oil up to 2.0%. Soluble in water at less than 0.01%. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

STANDARD PACKAGING: 55 lbs (25 kg) cartons.

STORAGE CONDITIONS: Store in a cool, dry and well-ventilated place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

SHELF LIFE: Best if used within 12 months from the date of manufacture.

HANDLING: Avoid all personal contact. Observe good personal hygiene. For additional information, it is advised to consult the Safety Data Sheet (SDS) for **NA-LUBE AW-6509**.

REGISTRATION: Please refer to Section 15 of the Safety Data Sheet for information.

For Samples or Technical Service, contact King Industries or your King representative.

King Industries, Inc.
Science Road
Norwalk, CT 06852-0588
Tel: 203-866-5551
Fax: 203-866-0425
E-mail: LAD@kingindustries.com

King Industries International, Inc.
Science Park 402,
1098 XH Amsterdam
The Netherlands
Tel: +31-20-723-1970
E-mail: info@kingintl.nl

NA-LUBE® is a registered trademark of King Industries, Inc.

v:\lad\TechnicalLiterature\CurmtPDS\NA-LUBE AW\AW6509_02
Revision date:: 15 JANUARY 2015

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.