

Additives for coatings and printing inks
DISPARLON®

(Aug. 2010)

SAMPLE REQUEST

DISPARLON® AQ-200
(Leveling agents for water-based systems)

DISPARLON AQ-200 is leveling agent based on amine salt of acrylic copolymer, designed to disperse or to be soluble uniformly in the paint to improve leveling of the film. These acrylic type products improve leveling of the film keeping good re-coatability but also improve flooding of pigment and orientation of metallic pigments.

APPLICATIONS:

DISPARLON AQ-200 is recommended for water-borne baking systems including Alkyd/Melamine, Acrylic/Melamine and Polyester/Melamine systems.

ADDITIVE LEVEL: 0.3% to 1.0% by weight on total paint.

INCORPORATION: Post-addition at let down stage is recommended.

TYPICAL PROPERTIES: (This is not for specification purpose.)

Appearance	Amber
Active component	20.0%
Solvent	Butyl cellosolve
S.P.* of acrylic copolymer	10.73
S.T.** of acrylic copolymer	30.7 (dyn/cm)
PH	9.0

- Solubility parameter, **Surface tension

Distributed by:
King Industries, Inc.
Science Road, Norwalk CT 06852
Ph: 203-866-5551



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079