

Name	Deogrip Micro S		
Description	Softtouch additive, matting- and antislip agent		
Composition	radically cross-linked modified castor oil dispersed in butyl acetate		
Appearance	white to yellowish dispersion		
Analytical values			
Solids content [%]	DIN EN ISO 3251		30 - 32
Density at 25°C [g/cm ³]	DIN ISO 787 T10A		0.94 – 0.98
Dosage [%]			5 - 15
Supply Form			25 kg in steel pails
Storage Stability			
In originally sealed package in cool and dry places			min. 1 year

Classification and Labelling

Deogrip Micro S is labelled as “flammable”. For more detailed information, please refer to our Material Safety Data Sheet.

Behaviour and Effects

Softtouch additive, matting- and antislip agent for solvent based systems.

Typical dosage ranges from 5 to 15 %, but can deviate in single cases. Due to the usage of Deogrip Micro S it is possible to reach exceptional effects on the surface.

These effects, depending on the processing and total recipe, can result in a soft, flexible to a good grip, rubbery surface.

Due to the raw material, based on renewable resources, Deogrip Micro S is suitable to attain an environmentally friendly matting effect.

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.