

Product Data Sheet

K-CORR[®] SA-300

SAMPLE REQUEST



Science Road
Norwalk, CT 06852
(800) 431-7900
Fax: (203) 866-0425
E-Mail: lad@kingindustries.com

K-CORR SA-300 is an ashless rust inhibitor for industrial and automotive lubricants, greases and rust preventive fluids.

CHEMICAL

COMPOSITION: Proprietary alkylated organic acid/ester chemistry in light mineral oil.

APPEARANCE: Clear amber viscous liquid.

TYPICAL

PROPERTIES:	Viscosity @ 40°C (ASTM D 445, DIN 51550)	3194 mm ² /s (cSt)
	Viscosity @ 100°C (ASTM D 445, DIN 51550)	40 mm ² /s (cSt)
	Density @ 15.6°C (ASTM D 4052)	0.98 g/ml
	Weight Per Gallon @ 25°C	8.1 lbs
	Acid Number, TAN (Potentiometric)	180 mg KOH/g
	Mineral Oil Content	~ 25%
	Flash Point, COC (ASTM D 92, DIN 51376)	160°C (320°F)

Note: The above analytical data are not specifications.

	<u>Typical Treat Levels</u>
APPLICATIONS: Hydraulic Fluids	0.03% - 0.2%
Circulating Oils	0.03% - 0.2%
Paper Machine Oils	0.05% - 0.3%
Greases	0.7% - 3.0%
Industrial and Automotive Gear Oils	0.10% - 0.5%
Rust Preventive Fluids	2.0% - 15.0%

K-CORR SA-300 is a highly efficient ashless rust inhibitor with outstanding demulsification properties. **K-CORR SA-300** is recommended for formulating high performance ashless circulating and steam turbine oils, hydraulic oils, paper machine oils, industrial and automotive gear oils as well as greases. **K-CORR SA-300** can also be used as a rust inhibitor in fuels and is also suitable for formulating ashless rust preventive fluids.

ADVANTAGES:

- * Outstanding ashless acidic rust inhibitor
- * Excellent demulsification properties
- * Good thermal and hydrolytic stability
- * Soluble in highly paraffinic and synthetic base oils
- * Effective at very low treat levels
- * Excellent compatibility with other functional additives

(see reverse side)

K-CORR[®] SA-300

TEST RESULTS: Technical reports are available from King Industries and can be requested by contacting the offices shown below.

SOLUBILITY: Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

STANDARD PACKAGING: 440 lbs (200 kg) closed head drum.

STORAGE CONDITIONS: Store in a cool dry place away from any direct sources of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

SHELF LIFE: Best if used within 18 months from the date of manufacture.

HANDLING: Avoid all personal contact. Observe good personal hygiene. For additional information, it is advised to consult the Safety Data Sheet (SDS) for **K-CORR SA-300**.

REGISTRATION: Please refer to Section 15 of the Safety Data Sheet for information.

For Samples or Technical Service, contact King Industries or your King representative.

King Industries, Inc.
Science Road
Norwalk, CT 06852-0588
Tel: 203-866-5551
Fax: 203-866-0425
E-mail: LAD@kingindustries.com

King Industries International, Inc.
Science Park 402,
1098 XH Amsterdam
The Netherlands
Tel: +31-20-723-1970
E-mail: info@kingintl.nl

K-CORR[®] is a registered trademark of King Industries, Inc.

v:\lad\TechnicalLiterature\CumtTDS\KCORR\SA-300_04
Revision date: 02 APR 2015

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.