

Additives for coatings and printing inks
DISPARLON[®]

IT-0273E

Sep. '10

DISPARLON[®] 6300
(Anti-sagging/Settling agent)

DISPARLON[®] 6300 is a powdered thixotropic agent based on amide wax for heavy duty paints. Being 100% active, this product is favorable not only in cost/performance, but because it offers excellent recoatability. Dispersed and activated with the heat generated during grinding this product activates so easily that it finds applications in a wide variety of formulations.

ADVANTAGES

- Excellent performance in non solvent epoxy systems with benzyl alcohol.
- Low temperature activation
- Strong anti-sagging.
- Maintained anti-settling.
- No seeding in paints during storage.
- Excellent recoatability.
- 100% organic, and in powdered form.

APPLICATIONS

DISPARLON[®] 6300 is specifically recommended for solvent-free epoxy paint.

INCORPORATION

Additive level: 0.5 ~ 2.0 % by wt.
Method: Grind with mill base at 50 ~ 70 °C.

TYPICAL PROPERTIES

Appearance	White to light yellow powder
Bulk density	0.20
Average particle size	15 μ
Melting point	125 °C
Acid value	Max. 20
Amine value	Max. 5
Specific Gravity	1.0 g/cm ³

Distributed by:
King Industries, Inc.
Science Road, Norwalk, CT 06852
Ph: 203-866-5551



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079