

Additives for coatings and printing inks
DISPARLON[®]

IT-5072E
(Oct. 2010)

DISPARLON[®] A603-20X
(Anti-Sagging/Anti-Settling agent)

DISPARLON A603-20X is an alcohol free thixotropic agent developed for isocyanate cured paint systems. Being pre-activated, **A603-20X** can perform as well as 6900-20X but should be incorporated in the millbase. **A603-20X** is supplied in a paste form.

ADVANTAGES

- Alcohol free, no reaction with isocyanate.
- Strong anti-sagging/settling
- Non-seeding
- No affect on pot-life.

APPLICATIONS

DISPARLON A603-20X is recommended for isocyanate cured systems such as polyurethane, acrylic/urethane, tar/urethane and epoxy/urethane systems.

(Don't use in the oil based systems, such as alkyd/melamine and other alkyd systems)

INCORPORATION

- Additive level : 1.0 ~ 5.0 % by weight of total formulation (finished paint)
Method : Disperse **A603-20X** sufficiently in the millbase using a sand grind mill or a high-speed dissolver.

TYPICAL PROPERTIES

- Appearance : White to light yellow paste
Non-volatile matter : 20 % by wt.
Solvents : Xylenes

Distributed by:

King Industries, Inc.

Science Road, Norwalk, CT 06852

Ph: 203-866-5551



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079