

Additives for coatings and printing inks
DISPARLON[®]

IS-9268E-4
(Oct. 2010)

DISPARLON[®] LS-430
(Leveling/Anti-cratering agents)

DISPARLON LS-430 is a surface control agent based on a specially prepared silicone polymer. This product has the unique ability to eliminate cratering caused by various kinds of dirt/stain or spray mists.

ADVANTAGES

- Eliminate cratering and film defects due to various contaminants.
- Excellent leveling & wetting

APPLICATIONS

DISPARLON LS-430 is recommended for water-borne systems and UV-cured systems.

INCORPORATION

Post addition to finished paint is recommended.

Recommended levels : 0.1 ~ 1.0 % by weight of finished paint.

TYPICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Non-volatile matter	50 % by wt.
Density	1.02 g/cm ³
Solvent	Propylene glycol monomethyl ether acetate

Distributed by:
King Industries, Inc.
Science Road, Norwalk, CT 06852



Kusumoto Chemicals, Ltd.
11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN
(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

Copyright© 2010 Kusumoto Chemicals, Ltd. All rights Reserved.

Ph: 203-866-5551



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See MSDS for safety handling before to use.