

Additives for coatings and printing inks
DISPARLON[®]

(Apr. 2010)

DISPARLON[®] SPL-93

(Slipping/Leveling agent)

DISPARLON SPL-93 is a silicone based slip/leveling agent. **DISPARLON SPL-93** has excellent compatibility in formulations and does not cause haze, improves slipping, scratch resistance, and anti-blocking properties. It also prevents cratering, and pin-holes that come from contamination, taking full advantage of its excellent leveling properties.

ADVANTAGES

- Good leveling & DOI.
- Prevent crater & fish eye.
- Good dispersability and stability on ageing in paint systems.

APPLICATIONS

DISPARLON SPL-93 can be used in all solvent based systems and is especially recommended for wood, architectural and industrial top coatings such as alkyd melamines, acrylic melamines, and acrylic urethanes.

INCORPORATION

Recommended levels : 0.2 ~ 2.0 % by wt. of paint.

Method : Post addition on high speed dissolver is recommended.



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

TYPICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Non-volatile	15 % by wt.
Density	0.89 g/cm ³
Solvent	Xylene

Distributed by:
King Industries, Inc.
Science Road, Norwalk, CT 06852
Ph: 203-866-5551



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079