

Additives for coatings and printing inks
DISPARLON[®]

Sep. 2010

DISPARLON[®] SPX-43
(Defoaming agent for non-aqueous paints)

DISPARLON[®] SPX-43 is a defoaming agent based on a silicone developed for ambient cured coating systems. The product is particularly effective in unsaturated polyester resin based formulations and can quickly eliminate foam generated in any type of coating application as well as the paint production process.

ADVANTAGES

- Highly effective in unsaturated polyester formulations.
- Quick defoaming in both spray and roller applications.
- Eliminates foam during paint production.
- Can be used in a broad type of ambient cured coatings.
- Compatible with a broad type of resins.

APPLICATIONS

DISPARLON[®] SPX-43 is recommended for ambient cured systems based on alkyd, acrylic, urethane and epoxy resins and particularly for unsaturated polyester resin systems containing amide wax based thixotropic agents.

INCORPORATION

Additive levels : 0.2 ~ 1.0 % by wt. of finished paint

Method : Post-addition is recommended

TYPICAL PROPERTIES



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

Appearance Light yellow liquid

Active..... 1 % by wt.

Solvent MIBK/Xylene

Distributed by:
King Industries, Inc.
Science Road, Norwalk, CT 06852
Ph: 203-866-5551



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079