

Product Data Sheet

K-CORR[®] SD-1223C (Formerly KX1223C)



Science Road
Norwalk, CT 06852
(800) 431-7900
Fax: (203) 866-0425
E-Mail: lad@kingindustries.com

K-CORR SD-1223C is a multifunctional ashless substituted polyamine surfactant / dispersant for lubricants that exhibits antioxidant and wear protection boosting properties.

CHEMICAL

COMPOSITION: Substituted polyamine.

APPEARANCE: Viscous brown liquid.

TYPICAL

PROPERTIES:	Nitrogen Content (ASTM D 5291)	6.6%
	Base Value (ASTM D 2896)	140 mg KOH/g
	Viscosity @ 100°C (ASTM D 445, DIN 51550)	60 mm ² /s (cSt)
	Density @ 15.6°C (ASTM D 4052)	0.955 g/ml
	Weight Per Gallon @ 25°C	8 lbs
	Flash Point, COC (ASTM D 92, DIN 51376)	160°C min
	Mineral Oil Content	none

Note: The above analytical data are not specifications.

	<u>Typical Treat Levels</u>
APPLICATIONS:	
Rust Preventive Fluids	0.5% - 5.0%
Hydraulic Fluids	0.2% - 1.5%
Circulating Oils	0.2% - 1.5%
Paper Machine Oils	0.2% - 1.5%
Greases	0.5% - 2.5%
Industrial and Automotive Gear Oils	0.2% - 1.5%

K-CORR SD-1223C improves the solubility of polar additives in industrial lubricants while maintaining good demulsibility. **K-CORR SD-1223C** can provide some varnish and sludge control in industrial lubricant applications. The oxidative stability of vegetable oils can be improved by formulating with **K-CORR SD-1223C**. The 4-ball wear performance of lubricating oils can also be boosted with the addition of **K-CORR SD-1223C**.

ADVANTAGES:

- * **Effective at low treat levels**
- * **Minimal impact on demulsibility (lubricants)**
- * **Provides varnish and sludge control**
- * **Multifunctional, ashless surfactant/dispersant**

(see reverse side)

K-CORR[®] SD-1223C
(Formerly KX1223C)

TEST RESULTS: Technical reports are available from King Industries and can be requested by contacting the offices shown below.

SOLUBILITY: Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

STANDARD PACKAGING: 420 lbs (191 kg) closed head drum.

STORAGE CONDITIONS: Store in a cool dry place away from any direct sources of heat and moisture. Maximum recommended storage temperature: 50°C (122°F)

SHELF LIFE: Best if used within 1 year of the date of manufacture.

HANDLING: Avoid all personal contact. Observe good personal hygiene. For additional information, it is advised to consult the Safety Data Sheet (SDS) for **K-CORR SD-1223C**.

REGISTRATION: Please refer to Section 15 of the Safety Data Sheet for information.

For Samples or Technical Service, contact King Industries or your King representative.

King Industries, Inc.
Science Road
Norwalk, CT 06852-0588
Tel: 203-866-5551
Fax: 203-866-0425
E-mail: LAD@kingindustries.com

King Industries International
Noordkade 64, 2741 EZ Waddinxveen
The Netherlands
Tel: 31-182-631360
Fax: 31-182-621002
E-mail: info@kingintl.nl

K-CORR[®] is a registered trademark of King Industries, Inc.

v:\lad\TechnicalLiterature\CurntTDS\K-CORR\SD-1223C_02
Revision date: 09 JUNE 2014

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.