



PERFORMANCE BLENDS *— with —*

NA-LUBE[®] BL SERIES

Ashless Packages for Industrial Lubrications

King Industries, Inc. has been developing and offering high performance additives since 1932. Our technical and marketing teams have been helping customers solve challenging formulating problems with the use of our NA-SUL®, K-CORR® and NA-LUBE® additives.

Awareness of synergies between additives has lead us to develop special blends that incorporate the most desirable features and benefits of a wide range of specialty additives. The **NA-LUBE BL Series** is comprised of high performance, ashless blends and packages for use in premium industrial lubricants.

NA-LUBE® BL Series

R&O

BL-1208

Hydraulic Oil

BL-1232 EL

BL-1300FG

BL-1400

Compressor/
Hydraulic Oil

BL-1200

Industrial Gear Oil

BL-1208 + AW-6310

NA-LUBE BL-1500 EL

NA-LUBE®

Product Descriptions

R&O, *pg. 3*

NA-LUBE BL-1208

General purpose rust and oxidation additive package that offers outstanding antioxidation performance for hydraulic, turbine and circulating oils.

Hydraulic Oil, *pg. 4-5*

NA-LUBE BL-1232 EL

Environmentally friendly multifunctional additive package designed for use in ester-based lubricants. Eligible for the European Ecolabel.

NA-LUBE BL-1300FG

Multifunctional rust and oxidation inhibiting additive package for food grade circulating oils, hydraulic fluids and gear oils.

NA-LUBE BL-1400

Additive package for antiwear hydraulic fluids that can be used to formulate fluids that meet Parker Hannifin (Denison) HF-0, HF-1 and HF-2 requirements.

Compressor/ Hydraulic Oil, *pg. 5*

NA-LUBE BL-1200

Multifunctional additive package for use in industrial oils. Offers outstanding performance for use in premium compressor oils.

Industrial Gear Oil, *pg. 6*




BL-1208 + AW-6310

Using BL-1208 R&O package **plus** AW-6310 to formulate gear oils meets AGMA 9005-E02 specifications.

NA-LUBE BL-1500 EL

Environmentally friendly additive package for use in ester-based gear oils that meets DIN 51517, Part 3. Eligible for the European Ecolabel.

NA-LUBE BL-1208 is a multifunctional, general purpose, ashless R&O additive package for industrial oils. Benefits include:

-  Excellent antioxidation properties
-  Good antiwear and anticorrosion performance
-  Can be used as a building block for formulating lubricant packages for other applications

NA-LUBE BL-1208 has been evaluated in API Group I, II, III, and IV base oils at 0.7% by weight. The excellent antioxidation performance shown in the table below varies with the base oil. The results for other significant R&O properties are similar for the four oils:

NA-LUBE BL-1208 R&O Performance in Base Oils

	Group I, II, III, IV
Synthetic Seawater Rust (ASTM D665B)	All pass
Copper Corrosion (ASTM D130) 3 hours, 100°C	1a - 1b
Demulsibility (ASTM D1401)	Separation in 30 minutes max
Four Ball Wear (ASTM D4172) 75°C, 40 kgf, 1 hour, 1200 rpm	0.4 - 0.5 mm scar diameter

NA-LUBE BL-1208 Antioxidant Performance in Base Oils

	Group I	Group II	Group III	Group IV
	With 0.7% NA-LUBE BL-1208			
RPVOT (ASTM D2272) Lifetime (minutes)	600	1,500	1,740	2,200
TOST (ASTM D943) Time (hours)	3,600	>10,000	>12,000	>12,000

NA-LUBE BL-1208 can also be used to formulate general purpose R&O oils based on triglycerides. In addition to the results noted above for rust, copper corrosion, demulsibility, and wear, the RPVOT results for two common vegetable oils are shown below:

NA-LUBE BL-1208 Antioxidant Performance in Vegetable Oils



	Canola Oil	Canola Oil + BL-1208	Soybean Oil	Soybean Oil + BL-1208
Treat Level, %	--	2.2	--	1.8
RPVOT (ASTM D2272) Lifetime (minutes)	14	100	17	290

High oleic content vegetable oils may provide improved oxidation stability. Selective synthetic ester base oils can achieve significant improvement in oxidative stability when used in environmentally friendly fluids. Results are available.

Specialty Packages for Hydraulic Oils

NA-LUBE® BL-1232 EL is an ashless, multifunctional additive package specifically designed for use in ester-based systems, including hydraulic fluids. NA-LUBE BL-1232 EL, when used as a single additive, qualifies for use in a final product eligible for the **European Ecolabel** at a concentration up to 1.8% by weight. NA-LUBE BL-1232 EL also qualifies for use in Environmentally Acceptable Lubricants (EALs) for Vessel General Permit (VGP) compliance.

Ecolabel
Compliance



- ✔ Excellent AFNOR and DIN filterability
- ✔ Excellent antiwear and anticorrosion performance
- ✔ Good antioxidation properties
- ✔ Good SRE-NBR seal compatibility

NA-LUBE BL-1232 EL Performance in Saturated Ester

	Specification DIN ISO 15380	Saturated Ester	
		Neat	w/ 1.8% BL-1232 EL
RPVOT (ASTM D2272) Lifetime (minutes)	--	<50	750
Dry TOST (ASTM D943 Modified) Acid # (mg KOH/g) Time (hours)	TAN <2.0 1,000	<0.1 100	0.25 5,880
Vickers 104C Vane Pump Weight loss ring (mg) Weight loss vanes (mg)	120 max 30 max	-- --	4.6 7.6
FZG A/8.3/90 (ASTM D5182) Damage load stage	10 min	--	>12

Food Grade
Approvals



NA-LUBE BL-1300FG is a multifunctional rust and oxidation inhibiting additive package designed for use in the food processing industry. Depending on the food grade base oil used, the recommended treat level is 1.0% to 2.3% by weight.



- ✔ Effective in most food grade base oils
- ✔ Outstanding oxidation and corrosion protection
- ✔ Excellent demulsibility and wet filtration
- ✔ Excellent Four Ball Wear and FZG performance
- ✔ Passes the Vickers 104C Vane Pump test at 1.5 % in PAO 8

NA-LUBE® BL-1200 offers outstanding performance in compressor fluids, turbine fluids, hydraulic fluids, circulating oils and industrial gear oils.

NA-LUBE BL-1200 Performance




	Group II	Group IV
	With 0.75% BL-1200	
RPVOT (ASTM D2272) Lifetime (minutes)	1,400	1,500
TOST (ASTM D943) Time (hours)	> 7,600	> 7,600

	Group I
	With 0.75% BL-1200
Vickers 104C Vane Pump Weight loss ring (mg) Weight loss vanes (mg)	13 6



Additional test results are available in Group I, II, III and IV oils.
Data with 0.6% treat on request.

NA-LUBE BL-1400 is a fully-formulated, ashless additive package for antiwear hydraulic fluids. It can be used to formulate fluids that meet Parker Hannifin (Denison) HF-0, HF-1 and HF-2 requirements.

-  Excellent thermal and hydrolytic stability
-  Good demulsibility
-  High load carrying capacity

NA-LUBE BL-1400 Denison and Vickers Performance in Group I and Group II Oils

	0.6% BL-1400	0.6% BL-1400
	Group I	Group II
Hydrolytic Stability (ASTM D2619) Copper loss (mg/cm ²) Acidity of water layer (mg KOH/g)	0 2.13	0 2.26
Denison Filterability Procedure A dry (seconds) Procedure B with water (seconds)	169 299	183 292
Vickers 104C Vane Pump Weight loss ring (mg) Weight loss vanes (mg)	2.1 4.1	-- --

Packages for Industrial Gear Oils






NA-LUBE® BL-1208 can be used as a building block for formulating lubricant packages for other applications, including EP industrial gear oils. The AW/EP booster, **NA-LUBE AW-6310**, can be added to NA-LUBE BL-1208 to fulfill the AGMA 9005-E02 Industrial Gear Oil Specification.

NA-LUBE BL-1208 Formulating Modification for Industrial Gear Oil

	0.7% BL-1208 0.3% AW-6310
	ISO VG 220
FZG A/8.3/90 (ASTM D5182) Damage load stage	>12
Gear Oil Oxidation (ASTM D2893) Viscosity increase (%)	2.4
Demulsibility (ASTM D2711) Procedure B Emulsion (ml) Total free H ₂ O (ml) Water in oil (%)	<0.1 87 0.40

Ecolabel Package for Industrial Gear Oils

NA-LUBE BL-1500 EL is an environmentally friendly, multifunctional, ashless additive package specifically designed for ester-based industrial gear oils. When used as a single additive with an approved base fluid, the final product is eligible for the **European Ecolabel** listing.

-  Compliance with Ecolabel criteria as a single additive up to 1.8% by weight
-  Excellent antiwear and anticorrosion performance
-  Good antioxidation performance
-  1.8% NA-LUBE BL-1500 EL in appropriate saturated ester meets DIN 51517 Part 3
-  FZG A/8.3/90 damage load stage >12





YOUR PARTNER IN SUCCESS — *with our* — **TECHNICAL SERVICE**

Developing high performance lubricants, greases, and rust preventives requires extensive testing. King Industries offers a broad range of ASTM, DIN, and IP capabilities with experienced personnel to support your formulations. Our Technical Service provides rigorous performance testing, expert guidance, and state of the art equipment. Always complimentary, fast, and confidential.

Featured Test Capabilities:

FE8



FZG



SRV



**LEARN
MORE:**





Data Disclaimer

Properties presented in this brochure are averages derived from typically twenty production lots. Product properties are subject to normal manufacturing and testing tolerances. Further information can be obtained from the certificates of analysis for each product.

Contact Information

United States

World Headquarters

King Industries, Inc.

Science Road

Norwalk, CT 06852

USA

Phone: 203-866-5551

Email: lad@kingindustries.com

Europe

King Industries International

Dr. Dagmar Gartz

Science Park 402

1098 XH Amsterdam

The Netherlands

Phone: +31 20 723 1970

Email: dgartz@kingindustries.com

Asia / Pacific

China Sales Office

Dr. Hui Wang

Dalian Mingruida Technical Consulting Co., Ltd

Building 51, 20 Shuxiang Street

Dalian, China

Phone: 86-15941108485

Email: Hui.Wang@kingindustries.com



Specialty Chemicals

Since **1932**

www.KingIndustries.com

KI_0126-V1

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. Such testing has not necessarily been done by King Industries, Inc. ("King"). The facts, recommendations and suggestions herein stated are believed to be reliable; however, no guaranty or warranty of their accuracy is made. EXCEPT AS STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. KING SHALL NOT BE HELD LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES. Any statement inconsistent herewith is not authorized and shall not bind King. Nothing herein shall be construed as a recommendation to use any product(s) in conflict with patents covering any material or its use. No license is implied or granted under the claims of any patent. Sales or use of all products are pursuant to Standard Terms and Conditions stated in King sales documents.